



RA 2

65 W LED Sokak ve Cadde LED



Order Code : 3192916
Product Code : RA2 065D 40SC00 100 8K40

Product Data

Standard Features

Housing	: SW 306G painted aluminium injection housing
Diffuser	: Tempered transparent glass
Optic	: 100° lens
IP Grade	: IP66
Installation	: Pole mounted
Light Source	: Power LED


Optical & Electrical Features

Power Consumption	: 65.5 W
Final Luminous Flux	: 8405.6 lm
Efficacy	: 128.2 lm/W
Input Voltage	: 220-240 V AC
Frequency	: 50-60 Hz
Power Factor	: > 0,9
Surge Transient Protection	: 6 kV
Drive Current	: 1000 mA
Correlated Color Temperature	: 4000K
Color Rendering Index	: >70

Other Features & Conditions


Operating Temperature Range	: -40 °C/ +55 °C
Impact Resistance	: IK08
Led Life Time - L70	: > 145.000 saat @Ta= 55 °C

Photometric Curve



Optional Features

Correlated Color Temperatures	: 5000K, 6500K
DALI	: Yes , RF Control



RA 2

65 W LED Sokak ve Cadde LED Aydınlatma Armatürü

3192916 RA2 065D 40SC00 100 8K40

Dimensions (mm)


	a	b	h	d
Standard	639	310	104	85

Weight (kg)

Standard	6,7
----------	-----



Vertical Installation Brackets



- EAE, reserves the right to make changes without prior notice.



EAE Aydınlatma A.Ş.

İktisadi Organize Sanayi Bölgesi Eski Turgut Özal Caddesi No:20 Başakşehir / İSTANBUL-TÜRKYE Phone: +90 212 413 21 00 (pbx) Fax: +90 212 549 37 90
www.eaeaydinlatma.com.tr

Revision date: 28.12.2020